

A₂ - Hummingbird Automatic Dispenser



- ➡ Minimum Shot: 1/2000Y
- ➡ 100% Recirculation
- ➡ Suitable for Sample Paint Dispensing

SANTINT • CHINA

Add: Sangong & Xingyun Road,
Xingyang City, Zhengzhou City,
Henan Province, 450121 China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski, 1109,
G11 e 12 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vehele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

A₂ - Hummingbird FEATURES >>>

SANTINT
WHERE INNOVATION MEETS PRECISION



1 Double Pump Double Nozzle

1/2000Y(0.015ml)
Minimum Shot



2 100% Recirculation

100% recirculation technology. Timed recirculation makes the colorant noncondensing and prevents the nozzle from dryness and blockage & colorant from deterioration.



3 Box/Table Tinting

Saving PC cost; pre-installed software, shorter installation time



4 Calibration-free Piston Pump

Bluetooth/Wireless Module(Optional)



P1.1 Piston Pump
Sequential Dispensing

- Single Pump Standard Flow Rate: 600ml/min
- Single Pump Standard Efficiency: 200ml/min
*It depends on the product property

■ Minimum Shot: 1/2000Y(0.015ml) *It depends on the product property

■ Pump Capacity: 60ml ■ Stirring Speed: 20rpm

■ Canister Size: 1.8L / 2.3L POM
2.3L / 3.8L Stainless Steel(Optional)

■ NO. of Canisters: Up to 16

■ Max Can Size(DxH): 320x600mm

■ Machine Dimension(WxDxH): 707x848x1300mm

■ Packing Dimension(WxDxH): 830x990x1500mm

Loading Quantity 14 Pieces/20GP

■ Net Weight: 130kg

■ Rated Power: 100W

■ Gross Weight: 155kg

■ Power Supply: 220V/110V 50Hz/60Hz

A₂ - Hummingbird

Technical Parameters

