

AH1000

Automatic Dispenser



Net Efficiency : 1000ml/minX5

Minimum Shot : 1/1024Y (Yellow Oxide Included)

Repeatability : ★ ★ ★ ★ ★ (1/768Y)

★ ★ ★ ★ ☆ (1/1024Y)

Durability : Yellow Oxide >10000L ; Others >20000L



SANTINT • CHINA

Add: Sangong & Xingyun Road,
Xingyang City, Zhengzhou City,
Henan Province, 450121 China
Email: info@santint.com

SANTINT • HOLLAND

Add: Gieterij 28, 2211 XK
Noordwijkerhout, The Netherlands
Email: sales@santint-europe.com

SANTINT • POLAND

Add: 43 Szyszkowa Street,
02-285 Warsaw, Poland
Email: albert@santintpoland.com

SANTINT • U.S.A

Add: 2000 Bloomingdale Road,
Suite 205, Glendale Heights,
IL 60139, U.S.A
Email: info@santintusa.com

SANTINT • BRAZIL

Add: Av. Rosa Kasinski, 1109,
G11 e 12 Capuava, Mauá,
SP - Brasil CEP 09380-128
Email: marcos@santint.com

SANTINT • INDIA

Add: H.No.692, Gala No.04, Print
World Industrial Complex,
Bhatale, Vhele Village, Opposite
Balaji Compound, Bhiwandi,
Maharashtra - 421302
Email: nick@santint.com

AH1000 FEATURES>>>



1

Self-calibration

P6 pump starts from zero position for each dispensing.



2

Blockage Warning No Tube Explosion


No tube explosion, longer durability; Alarm when nozzles blocked



3

Recirculation


No sedimentation, drying or block in tubes, minimizing malfunction



4

Water Circulation Humidifier

Minimizing nozzle blockage



5

Three-Way Valve

Valve
Temporary blocker
Air Exhauster



6

Multi-functional Roller Conveyor (Optional)



- Minimum Shot: 1/1024Y(0.029ml) *It depends on the product property
- Dispensing Type: 5 Channels Simultaneous (max.)
- Single Pump Standard Efficiency: 1000ml/min *It depends on the product property

- Stirring: 1min/ h
- Stirring Speed: 15r/min
- Recirculation: Every 4 Hours *Timed stirring and timed recirculation's time interval customizable
- Recirculation System: Standard
- Automatic Can Table: Standard
- Humidifier: Standard

- NO. of Canisters: Up to 32
- Canister Size: 6L/12L/22/50/200L
- Canister Material: POM、Stainless Steel(Optional)
- Dimension(WxDxH): 1690x1210x1320mm

- Rated Power: 400W
- Power Supply: 220V/110V 50Hz/60Hz

AH1000
<<<Technical Parameters

